






SPLIT-LOCK BAR


Patent number: WO9607016
Publication date: 1996-03-07
Inventor: SCOTT-SMITH PHILIP ANTHONY [AU]
Applicant: SCOTT SMITH PHILIP ANTHONY [AU]
Classification:
- international: E21D21/00
- european: E21D21/00N
Application number: WO1995AU00546 19950828
Priority number(s): AU1994PM07725 19940829

Cited documents

 CA94889E
 US25700C
 DE11115E
 DE22568E
 DE352524
more >>

Abstract of WO9607016

A split-lock bar (10) for use in fixing into a hole, such as in a rock face for securely fixing a face plate or hook or the like onto the rock face. The split-lock bar (10) has a flared head (20) which carries a split collar (14) which is compressed as the split-lock bar (10) is forced into the hole and expands as it moves along the flared head (20) as force is applied to attempt to remove the split-lock bar (10) from the hole.



Data supplied from the **esp@cenet** database - Worldwide

BEST AVAILABLE COPY

PCT

INTELLECTUAL PROPERTY
International B

INTERNATIONAL APPLICATION PUBLISHED UNDER



(51) International Patent Classification ⁶ :

E21D 21/00

A1

(11) In

WO 9607016A1

(43) International Publication Date:

7 March 1996 (07.03.96)

(21) International Application Number: PCT/AU95/00546

(22) International Filing Date: 28 August 1995 (28.08.95)

(30) Priority Data:

PM 7725

29 August 1994 (29.08.94)

AU

(71)(72) Applicant and Inventor: SCOTT-SMITH, Philip, Anthony [AU/AU]; 117 Federal Street, Boulder, W.A. 6032 (AU).

(74) Agent: GIRAUDO, Clinton; P.O. Box 265, Cottesloe, W.A. 6011 (AU).

(81) Designated States: AM, AT, AU, BB, BG, BR, BY, CA, CH, CN, CZ, DE, DK, EE, ES, FI, GB, GE, HU, IS, JP, KE, KG, KP, KR, KZ, LK, LR, LT, LU, LV, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, TJ, TM, TT, UA, UG, US, UZ, VN, European patent (AT, BE, CH, DE, DK, ES, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, ML, MR, NE, SN, TD, TG), ARIPO patent (KE, MW, SD, SZ, UG).


Published

With international search report.

(54) Title: SPLIT-LOCK BAR

(57) Abstract

A split-lock bar (10) for use in fixing into a hole, such as in a rock face for securely fixing a face plate or hook or the like onto the rock face. The split-lock bar (10) has a flared head (20) which carries a split collar (14) which is compressed as the split-lock bar (10) is forced into the hole and expands as it moves along the flared head (20) as force is applied to attempt to remove the split-lock bar (10) from the hole.



FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AT	Austria	GB	United Kingdom	MR	Mauritania
AU	Australia	GE	Georgia	MW	Malawi
BB	Barbados	GN	Guinea	NE	Niger
BE	Belgium	GR	Greece	NL	Netherlands
BF	Burkina Faso	HU	Hungary	NO	Norway
BG	Bulgaria	IE	Ireland	NZ	New Zealand
BJ	Benin	IT	Italy	PL	Poland
BR	Brazil	JP	Japan	PT	Portugal
BY	Belarus	KE	Kenya	RO	Romania
CA	Canada	KG	Kyrgyzstan	RU	Russian Federation
CF	Central African Republic	KP	Democratic People's Republic of Korea	SD	Sudan
CG	Congo	KR	Republic of Korea	SE	Sweden
CH	Switzerland	KZ	Kazakhstan	SI	Slovenia
CI	Côte d'Ivoire	LI	Liechtenstein	SK	Slovakia
CM	Cameroon	LK	Sri Lanka	SN	Senegal
CN	China	LU	Luxembourg	TD	Chad
CS	Czechoslovakia	LV	Latvia	TG	Togo
CZ	Czech Republic	MC	Monaco	TJ	Tajikistan
DE	Germany	MD	Republic of Moldova	TT	Trinidad and Tobago
DK	Denmark	MG	Madagascar	UA	Ukraine
ES	Spain	ML	Mali	US	United States of America
FI	Finland	MN	Mongolia	UZ	Uzbekistan
FR	France			VN	Viet Nam
GA	Gabon				

TITLE

SPLIT-LOCK BAR

FIELD OF THE INVENTION

The present invention relates to a split-lock bar particularly, although not exclusively, envisaged for use in fixing bolts and the like into holes such as in walls, rock faces, metal and wooden structures and the like. Mostly the split-lock bar is envisaged for use in mining situations where the fixing of large bolts into walls and rock faces is common place and is associated with some difficulties.

BACKGROUND OF THE INVENTION

In the mining industry it is known to use expandable bolts to fix into holes drilled in a rock face to fix retaining plates to the rock face (for stabilising the rock face against collapse or rock slide). A disadvantage of the expansion bolts is that the degree of securement of the bolt into the hole is limited to the nature of the expansion.

It is also known to grout bolts into such holes. A disadvantage of the use of grout is that the degree of securement of the bolt into the hole is limited to the integrity and strength of the grout.

It is also known to use expansion bolts in holes in bricks used in buildings, but with the same disadvantage. In metal and wooden structures bolts are usually threaded into holes or otherwise driven into the structure under force of a hammer or the like.

I have discovered that improved securement of a bolt into a hole can be achieved by using a split collar which contracts as the bolt is driven into the hole and which expands to jam into the hole when force is applied to withdraw the bolt from the hole.

SUMMARY OF THE INVENTION

Therefore, it is an object of the present invention to provide a split-lock bar which acts to jam into a hole when force is applied to withdraw the bar from the hole.

In accordance with one aspect of the present invention there is provided a split-lock bar for jamming into a hole, the split-lock bar comprising:

an elongate body having a free end with a flared head;

a retaining ring located about the elongate body and spaced apart from the free end;

a split collar located upon the elongate body between the free end and the retaining ring, the split collar being
5 moveable axially upon the elongate body between the retaining ring and the free end, and the split collar being able to be contracted as the split-lock bar is driven into the hole and the split collar being able to be expanded by movement of the flared head axially with respect to the split collar as force
10 is applied to withdraw the split-lock bar from the hole.

The present invention will hereinafter be described with particular reference to use in holes in rock faces, although it is to be understood that it is of general applicability.

BRIEF DESCRIPTION OF THE DRAWINGS

15 An exemplary embodiment of the present invention will now be described with reference to the accompanying drawings in which:-

Figure 1 is a perspective view, seen from above, of a split-lock bar in accordance with the present invention;

20 Figure 2 is a side view of the split-lock bar of Figure 1; Figures 3 and 4 are end views of the split-lock bar of Figure 1; and,

Figure 5 is a cross-sectional view of a split collar of the split-lock bar of Figure 1, shown to an enlarged scale.

25 DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENT(S)

In the drawings there is shown a split-lock bar 10 comprising an elongate body 12, a split collar 14 and a retaining ring 16.

The elongate body 12 has a free end 19 at which is located
30 a flared head 20. Typically, the elongate body 12 has a thread at its other end (not shown). The flared head 20 typically has a bevelled edge 22 to facilitate the introduction of the elongate body 12 into a hole, such as in a rock face. The threaded end of the elongate body 12 typically receives a nut
35 for securing a plate or the like to the rock face.

The split collar 14 is substantially cylindrical on its outer surface 30 and on its inner surface 32 has a tapered portion 34 and a cylindrical bore 36. The tapered portion 34 is tapered at substantially the same angle as the flaring of

the flared head 20. The cylindrical bore 36 is greater in diameter than the diameter of the elongate body 12 for allowing axial movement of the split collar 14 along the elongate body 12 in the vicinity of the flared head 20.

5 The split collar 14 has a split 38 disposed along its length and typically substantially parallel to the axis of the split collar 14. The split 38 is typically at least as wide as the difference in diameter of the elongate body 12 and the internal diameter of the cylindrical portion 36 of the inner
10 surface 32 of the split collar 14 so as to allow contraction of the split collar 14 about the elongate body 12 as the split-lock bar 10 is introduced into the hole. The split 38 thus allows the split collar 14 to reduce in diameter as the split-lock bar 10 is driven into the hole and to increase in diameter
15 as force is applied to withdraw the split-lock bar 10 from the hole.

The retaining ring 16 is typically cylindrical and is conveniently welded to the elongate body 12 at a distance from the free end 19. The split collar 14 is located between the
20 retaining ring 16 and the flared head 20 and is able to move axially along the elongate body 12 between the free end 19 of the elongate body 12 and the retaining ring 16. The retaining ring 16 bears against the split collar 14 as the split-lock bar 10 is driven into the hole for ensuring that the split collar
25 14 enters into the hole and remains in close proximity to the flared head 20. That is, the retaining ring 16 prevents the split collar 14 from sliding all the way along the elongate body 12 as the split-lock bar 10 is driven into the hole. It is essential to keep the split collar 14 in close proximity to
30 the flared head 20 so that the flared head 20 will cause the split collar 14 to expand and jam into the hole as an attempt is made to withdraw the split-lock bar 10 from the hole.

In use, a hole is drilled, in known manner, into the rock face. The hole is preferably drilled to a diameter which is
35 substantially the same as the external diameter of the split collar 14. The free end 19 of the split-lock bar 10 is then inserted into the hole. This insertion is facilitated with the aid of the bevelled edge 22. As the split collar 14 meets the entry to the hole the split collar 14 is forced back along the

elongate body 12 towards the retaining ring 16. When the split collar 14 meets the retaining ring 16 it is prevented from slipping further along the length of the elongate body 12. The split-lock bar 10 is typically driven into the hole with a hammer or the like.

Once the split-lock bar 10 has been driven the desired distance into the hole force is applied to withdraw the split-lock bar 10 from the hole. Typically, this is achieved by threading a nut with a hook or the like to the threaded end of the elongate body 12 and pulling the hook in a direction out of the hole. This has the effect of causing the elongate body 12 to move in a direction out of the hole whilst the split collar 14 remains jammed into the hole. As the elongate body 12 moves with respect to the split collar 14 the flared head 20 rides along the tapered portion 34 of the split collar 14 and the split collar 14 becomes closer to the free end 19 of the elongate body 12. The movement of the split collar 14 with respect to the flared head 20 causes the split collar 14 to expand at the split 38. The expansion causes the split collar 14 to jam into the hole.

The amount of force of jamming of the split collar 14 into the hole increases as the amount of force on the elongate bar 12 for pulling the elongate bar 12 out of the hole increases. This is a major advantage of the split-lock bar 10 of the present invention.

Also, it is envisaged that the flared head 20 could be located (such as be threading or welding) upon the end of a hollow pipe. Similarly, the flared head 20 could be hollow so that grout could be pumped through the hollow pipe and through the flared head for increasing the force of engagement of the split-lock bar 10 into the hole.

Modifications and variations such as would be apparent to a skill addressee are considered within the scope of the present invention. For example, the split 38 in the split collar 14 could be shaped other than straight, such as, curved or slanted or the like. Also, a ridge could be provided on the tapered head for engaging with the split collar 14 for ensuring that the split collar 14 does not rotate upon the elongate body 12. This assists in ensuring that a nut can be threaded upon

the threaded end of the elongate body 12. The ridge could be located within the slot 38 or it could be located in a groove in the inner surface 32 of the split collar 14. Further, a bevelled edge could be provided on the leading edge of the slit
5 collar 14. Still further, a pattern could be provided on the outer surface 30 of the split collar 14 for increasing the frictional engagement of the split collar 14 with the hole. Still further

CLAIMS

1. A split-lock bar for jamming into a hole, the split-lock bar comprising:
 - an elongate body having a free end with a flared head;
 - 5 a retaining means located about the elongate body and spaced apart from the free end;
 - a split collar located upon the elongate body between the free end and the retaining means, the split collar being moveable axially upon the elongate body between the retaining
 - 10 means and the free end, and the split collar being able to be contracted as the split-lock bar is driven into the hole and the split collar being able to be expanded by movement of the flared head axially with respect to the split collar as force is applied to withdraw the split-lock bar from the hole.
- 15 2. A split-lock bar according to Claim 1, in which the flared head has a ridge disposed between the free end and the retaining means for inhibiting rotation of the split collar upon the flared head for allowing a threaded member such as a nut to be threaded onto the elongate body at its other end.
- 20 3. A split-lock bar according to Claim 1, in which the elongate body is hollow for allowing settable material to be pumped through the split-lock bar into the hole and about the flared head and the elongate body for setting the split-lock bar into the hole for increasing the force of fixing of the
- 25 split-lock bar into the hole.
4. A split-lock bar according to Claim 1, in which the split collar is substantially cylindrical on its outer surface and its inner surface has a tapered portion and a cylindrical bore, the tapered portion being tapered at substantially the same
- 30 angle as the flaring of the flared head for causing the split collar to expand as the split collar moves towards the free end, and the cylindrical bore being greater in diameter than the diameter of the elongate body for allowing axial movement of the split collar along the elongate body in the vicinity of
- 35 the flared head.

5. A split-lock bar according to Claim 4, in which the split collar has a split disposed along its length, the split being at least as wide as the difference in diameter between the elongate body and the internal diameter of the split collar so
5 that the split collar can be forced to contract about the elongate body as the split-lock bar is driven into the hole.
6. A split-lock bar according to Claim 4, in which the split collar has a pattern formed into its cylindrical outer surface for increasing the force of engagement of the split collar with
10 the hole.
7. A split-lock bar according to Claim 1, in which the free end has a bevel for facilitating the introduction of the split-lock bar into the hole.
8. A split-lock bar according to Claim 1, in which the split
15 collar has a bevel on its end proximate the free end for facilitating the introduction fo the split-lock bar into the hole

FIG. 1.




FIG. 2.




FIG. 3.




FIG. 4.





FIG. 5.



INTERNATIONAL SEARCH REPORTInternational Application No.
PCT/AU 95/00546**A. CLASSIFICATION OF SUBJECT MATTER**Int Cl⁶: E21D 21/00

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHEDMinimum documentation searched (classification system followed by classification symbols)
IPC E21D 21/00Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched
AU: IPC as above

Electronic data base consulted during the international search (name of data base and, where practicable, search terms used)

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	CA 948 898 A (WILLIAMS et. al.) 11 June 1975 Entire Document	1-8
X Y	US 2 570 003 A (PALMER) 2 October 1951 Entire Document	1, 4-6, 8 2, 7
Y	DE 1 111 580 A (UBEREIN) 8 February 1962 Drawing and relevant description	2, 7

☐ Further documents are listed in the continuation of Box C☐ See patent family annex

Special categories of cited documents:	
"A" document defining the general state of the art which is not considered to be of particular relevance	"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention
"E" earlier document but published on or after the international filing date	"X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone
"L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)	"Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art
"O" document referring to an oral disclosure, use, exhibition or other means	"&" document member of the same patent family
"P" document published prior to the international filing date but later than the priority date claimed	

Date of the actual completion of the international search
8 December 1995Date of mailing of the international search report
20 December 1995Name and mailing address of the ISA/AU
AUSTRALIAN INDUSTRIAL PROPERTY ORGANISATION
PO BOX 200
WODEN ACT 2606
AUSTRALIA Facsimile No.: (06) 285 3929Authorized officer
G.RAMACHANDRAN
Telephone No.: (06) 283 2117

C (Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT		
Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X Y	DE 2 256 822 A (JOST) 6 June 1974 Drawings and relevant description	1, 2, 5 3, 4, 6-8
Y	DE 3 525 244 A (HILTIAG) 15 January 1987 Drawing and relevant description	4
Y	DE 1 201 289 A (EMERY) 23 September 1965 Drawing and relevant description	6-8
A	AU 26 916/71 A (COBDEN - JONES MINING PTY. LTD.) 28 September 1972	
A	AU 4 020/51 A (152 879) (FREDERICK VERNER THOMPSON) 24 July 1952.	

INTERNATIONAL SEARCH REPORT

Information on patent family members

International Application No.

PCT/AU 95/00546

This Annex lists the known "A" publication level patent family members relating to the patent documents cited in the above-mentioned international search report. The Australian Patent Office is in no way liable for these particulars which are merely given for the purpose of information.

Patent Document Cited in Search Report				Patent Family Member			
CA	948898	DE	2105888	GB	1323031	JP	55018840
		SU	393845	US	3695045	ZA	7100333
		US	3837258				
DE	3525244	EP	213068	US	4730966		
DE	2256822						
AU	26916/71						
END OF ANNEX							

**This Page is Inserted by IFW Indexing and Scanning
Operations and is not part of the Official Record**

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

- ☐ BLACK BORDERS
- ☐ IMAGE CUT OFF AT TOP, BOTTOM OR SIDES
- ☐ FADED TEXT OR DRAWING
- ☐ BLURRED OR ILLEGIBLE TEXT OR DRAWING
- ☐ SKEWED/SLANTED IMAGES
- ☐ COLOR OR BLACK AND WHITE PHOTOGRAPHS
- ☐ GRAY SCALE DOCUMENTS
- ☐ LINES OR MARKS ON ORIGINAL DOCUMENT
- ☒ REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY
- ☐ OTHER: _____

IMAGES ARE BEST AVAILABLE COPY.

As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.